TEXTILE LUBRICANTS · FIBRE & YARN LUBRICANTS

PERFASOFT PJ.

PERFASOFT PJ is an aqueous micro-emulsion of amino silicone polymer developed as a single addition, resin-stable softening agent.

APPLICATION

- Padding (5-10g/ltr dilution)
- Exhaustion (0.5-1.0% at 40°C, 15-20 minutes, pH 6-6.5)
- Wool and cashmere knitwear
- Cotton
- Polyester/cotton blends
- Synthetics

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear, water-white liquid**
Solubility		**Totally water soluble**
pH (1% aqueous solution)		**4-6**
Ionic activity		**Non-ionic/cationic**

Typical values, not a specification.

PACK SIZES

25kg drums, 200kg drums, 1000kg IBC's

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963