SPECIALITIES · ANTIFREEZE & COOLANTS

POLAR FREEZE 1 MEG ANTIFREEZE.

A conventional mono-ethylene glycol coolant concentrate with established inhibitor technology, free from nitrites, amines and phosphates.

APPLICATION

- Mixed fleets on a conventional coolant standard
- Plant and industrial engines
- Systems needing documented coolant properties
- General automotive and commercial use

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010
ASTM	D3306
SAE	J1034
AFNOR	NF R15-601
BTC	Type 2
ECUNA	NC 956-16

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Blue liquid**
Density @ 15°C (ASTM D4052) g/mL min 1.110, max 1.145		**1.119**
Water Content (ASTM D1123) max 5	%wt	**4.3**
Reserve Alkalinity 0.1N HCl (ASTM D1121) mL		**20.5**
pH – 50% Vol Aqueous Solution (ASTM D1287) min 7.5, max 11		**7.8**
Boiling Point – Equilibrium Reflux (ASTM D1120) min 150	°C	**161**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963