SPECIALITIES · ANTIFREEZE & COOLANTS

POLAR FREEZE 3 VCS 5050.

Polar Freeze 3 VCS supplied ready mixed, protecting to -37 °C as received.

APPLICATION

- HGV fleet servicing and roadside top-up
- Depots eliminating dilution error
- Heavy duty diesel systems on ASTM D6210

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 13 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
DAF	74002
Cummins	CES 14603
MAN	324 Type SNF
Mercedes-Benz	325.3
MTU	MTL 5048
RENAULT	41-01-001-D
VAG	G12/G12+, TL 774-D/F
VOLVO	VCS 418-001
Suitable	for use where G30, G33 and G34 specification fluids are required

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Yellow Colour**
Frost protection	°C	**Use as received, protects to -37**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963