SPECIALITIES · ANTIFREEZE & COOLANTS

# POLAR FREEZE 5 SI-OAT (PURPLE) 50:50 ANTIFREEZE.

The pre-mixed, ready-to-use form of the Polar Freeze Si-OAT coolant, using Organic Acid Inhibitor/Low Silicate Technology to protect from frost damage down to -38°C, free of nitrites, amines, phosphates and borates.

## APPLICATION

- Aluminium alloy coolant systems, ready-to-use 50:50 dilution
- Passenger cars, light and heavy commercial vehicles, off-highway plant

### NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

## BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 11 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **BS** | 6580:2010 |
| **ASTM** | D6210, D3306 |
| **SAE** | J1034 |
| **AFNOR** | R15-601 |
| **Cummins** | CES 14603 |
| **MAN** | 324 Type Si-OAT |
| **Mercedes-Benz** | 325.6 |
| **MTU** | MTL 5048 |
| **SCANIA** | TB 1451 |
| **VAG** | G12++, TL 774-GG |
| | 40 specification fluid |

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Pink/Red colour** |
| Freeze protection @ 25% dilution<br>S.G. 1.032 | °C | **-12** |
| Freeze protection @ 33% dilution<br>S.G. 1.040 | °C | **-22** |
| Freeze protection @ 50% dilution<br>S.G. 1.065 | °C | **-38** |

Typical values, not a specification.

### PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963