SPECIALITIES · ANTIFREEZE & COOLANTS

POLAR FREEZE 6 XLC-OAT (ORANGE) 50:50 ANTIFREEZE.

The pre-mixed, ready-to-use form of the Polar Freeze XLC-OAT coolant, an Organic Acid Inhibitor Technology formulation free of nitrites, amines, phosphates, borates and silicates, protecting from frost down to -40°C.

APPLICATION

- Ready-to-use coolant systems in passenger cars, commercial vehicles and off-highway plant

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 17 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Orange/Red**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306
Chrysler	MS 9176
Cummins	85T8-2, 90T8-4
FORD	WSS-M97B44-D
GM/Saab	6277M, 1899M
John Deere	H24 B1/C1
Mack	014G
S	17004
MAN	248, 324 Type SNF
Mercedes-Benz	325.3 (concentrate), 326.3 (pre-mixed)
MTU	MTL 5048
PSA	Group B71 5110
Renault	41-01-001-D
VAG	G12/G12+, TL 774-D/F
Volvo	Penta VCSG30, G33 and G34 specification fluids

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963