SPECIALITIES · ANTIFREEZE & COOLANTS

POLAR FREEZE 7 HYBRID-NF GREEN ANTIFREEZE.

A hybrid-OAT coolant combining Organic Acid Inhibitor Technology with borate and silicate for heavy-duty diesel engines, free of nitrites, amines and phosphates, with superior silicate stabilisation against gel formation

APPLICATION

- Heavy commercial vehicle and off-highway plant coolant systems
- Light-duty use where this coolant specification is required

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 14 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Blue/Green colour**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306, D6210
AFNOR	NF R15-601
SAE	J 1034
Chrysler	MS-7170
Cummins	85T8-2
Deutz	DQC CA-14
FORD	ESD-M97B49-A
Iveco	Standard 18-1830
MB	325.00
MAN	324 Typ NF
SCANIA	LLC TB1451
VAG	G11, TL 774-C
	G48 specification fluid

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963