GREASES · AUTOMOTIVE GREASES

RED RUBBER GREASE.

A bentone-thickened, vegetable-oil-based grease for brake and hydraulic assembly.

> 260 °C	2 / 3	Red
Dropping point	NLGI grade	Colour

APPLICATION

- Brake caliper and cylinder assembly
- Rubber seals and boots
- Hydraulic system assembly
- Anywhere a mineral grease would swell the seal

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth grease**
Colour ASTM D1500		**Red**
NLGI Classification		**2 / 3**
Thickener		**Bentone**
Worked Penetration		**250 to 280**
Base Oil		**A blend of vegetable oils**
Dropping Point (ASTM D2265)	°C	**> 260**
Effect On Natural Rubber (volume change)	%	**+1% to +6**
Effect On Neoprene Rubber (volume change)	%	**-10% to + 10**
Steel Weight change mg/cm²		**0.2**
Aluminium alloy Weight change mg/cm²		**0.1**
Copper Weight change mg/cm²		**0.5**
Cast Iron Weight change mg/cm²		**0.0**
High Temperature Stability @ 120°C		**No polymerization**
Operating Temperature Range	°C	**-5°C to +120**

Typical values, not a specification.

PACK SIZES

500 g, 3 kg, 12.5 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963