TEXTILE LUBRICANTS · MACHINE LUBRICANTS

RING OIL 46.

RING OIL 46 is formulated for the lubrication of a wide variety of spinning and twisting rings, including sintered rings.

41.4-50.6 cSt	0.890	Below -5 °C
Viscosity @ 40°C	Specific Gravity @15.6	Pour point

APPLICATION

- Lubrication of ring spinning
- Solid and sintered rings

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Pale Amber Oil**
Specific Gravity @15.6°C		**0.890**
Viscosity @ 40°C	cSt	**41.4-50.6**
Pour Point ASTM D97	°C	**Below -5**
Cloud Point	°C	**>70**
Moisture	%	**0.5**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963