INDUSTRIAL OILS · INDUSTRIAL SPECIALITIES

ROCK DRILL OIL 320.

The heaviest-viscosity grade in the Rock Drill Oil range for pneumatic percussion equipment, combining strong EP/anti-wear protection with a tackiness additive that keeps an oil film on cylinder walls under constant air-

320 cSt	>225 °C	-39 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Air-operated rock drills, jackhammers and pile drivers
- Pneumatic tools: air saws, riveters and torque wrenches
- Mining, quarrying, construction and excavation equipment

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour & Appearance		**Brown liquid**
Density @ 20°C ISO 22241-2	kg/m³	**0.896**
Kinematic Viscosity @ 40°C	cSt	**320**
Flash Point ASTM D92	°C	**>225**
Pour Point ASTM D97	°C	**-39**

Typical values, not a specification.

PACK SIZES

20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963