INDUSTRIAL OILS · INDUSTRIAL SPECIALITIES

ROCK DRILL OIL ULTRA EP.

A synthetic-base range of rock drill oils across three viscosity grades, combining oxidation-resistant base stocks with rust, foam, extreme-pressure and tackiness additives for long, trouble-free service in air-operated

APPLICATION

- Pneumatic drills, jumbo drills, jackleg drills and jackhammers
- Small air tools, air motors and airline oilers

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance (all grades)		**Brown liquid**
Kinematic Viscosity @ 40 °C, ISO 100	cSt	**100**
Kinematic Viscosity @ 40 °C, ISO 220	cSt	**220**
Kinematic Viscosity @ 40 °C, ISO 320	cSt	**320**
Density @ 20 °C, ISO 100 / 220 / 320	kg/m^3	**0.889** / **0.896** / **0.899**
Flash Point, ISO 100 / 220 / 320	°C	**>220** / **>225** / **>230**
Pour Point, ISO 100 / 220	°C	**-39**
Pour Point, ISO 320	°C	**-42**

Typical values, not a specification.

PACK SIZES

20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963