INDUSTRIAL OILS · CHAIN LUBRICANTS

SARCHAIN HT 550G.

A graphited synthetic ester chain lubricant for the hottest chain applications there are.

APPLICATION

- Furnace and kiln conveyor chain
- Heat treatment line chain
- Very high temperature drive chain
- Chains running past 300 °C where nothing liquid survives

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Black liquid**
Base Fluid		**Synthetic ester**
Viscosity @ 40 °C	cSt	**220 min**
Specific Gravity @ 20 °C		**1.01**
Temperature Range		**10 to 225 °C as a fluid lubricant or up to 550 °C as a dry film lubricant**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963