METALWORKING FLUIDS · NEAT CUTTING OILS

# SARCUT CASF 10.

An extreme pressure neat cutting oil blended from solvent refined mineral oil using selected additives, affording a high level of lubricity and EP performance.

## APPLICATION

- deep hole boring
- broaching
- heavy duty tapping
- threading
- gear cutting

### NOT RECOMMENDED

- × **Machining of magnesium, or of aluminium where a low-pH fluid is required**
- × **Use as a hydraulic or slideway oil - cross-contamination will shorten sump life**

## BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind - free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Amber Fluid** |
| Specific Gravity @ 15.6°C | | **0.876** |
| Kinematic Viscosity @ 40°C | cSt | **9.2 – 11.00** |
| Sulphur | | **Yes – Active** |
| Chlorine<br>ASTM D808 | | **Yes** |
| Ester | | **Yes** |

Typical values, not a specification.

### PACK SIZES

25 L, 205 L, 1000 L IBC

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963