FOOD GRADE · FOOD GRADE RELEASE & ASSEMBLY COMPOUNDS

SARFOOD 3H GREASE.

The only product in the range carrying NSF 3H, and that category is the significant thing: 3H permits direct contact with food, not merely incidental contact.

APPLICATION

- Release agent on grills, ovens and loaf pans
- Chopping boards and butchery benches
- Direct food contact surfaces
- Bearings and slides in the same production area

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

NSF	3H, H1
USDA	1998 H1 Guidelines
FDA	listed ingredients
No	genetically-modified ingredients
Contains	no nut oil or derivatives

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**White grease**
NLGI Classification		**No.1**
Thickener		**Inorganic thickener**
Drop Point (IP 132)		**None**
Base Oil		**Blend of white oils**
Solid Lubricant		**Direct food additives**
Copper Corrosion (IP 112)		**Pass**
Water washout (ASTM DS1264) @ 38°C		**< 2% max.**
Dynamic Corrosion Resistance (EMCOR) (IP 220)		**0:0**
Four Ball (IP 239) Weld Load		**400 kg**
Operating Temperature Range	°C	**-30°C to + 120**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963