FOOD GRADE · FOOD GRADE RELEASE & ASSEMBLY COMPOUNDS

SARFOOD ASSEMBLY GREASE.

A high-solids food grade assembly paste, and the food plant answer to copper anti-seize - which cannot be used anywhere near product.

APPLICATION

- Anti-seize on threaded fasteners in food areas
- Assembly and running-in of bushes and bearings
- Small open plastic or metal gears
- Where a ceramic paste is specified

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 5 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

FDA	listed ingredients
NSF	and InS H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients
Contains	no nut oil or derivatives

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Off white smooth paste**
Carrier		**Synthetic Oil**
Base Oil Viscosity @ 40°C	cSt	**320**
Solid lubricant		**White lubricating solids**
EMCOR (IP 220)		**0:0**
Coefficient of friction		**0.12**
Water washout (ASTM D1264) @ 38°C		**< 1% max.**
Four Ball Weld Load (IP 239)		**600kg**
Operating Temperature Range (service lubricant)	°C	**-30°C to +150**
Operating Temperature Range (anti-seize lubricant)	°C	**-30°C to +100**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963