FOOD GRADE · FOOD GRADE HEAT TRANSFER OILS

SARFOOD HEAT TRANSFER OIL 32.

A food grade thermal fluid for closed circuit and pressureless heat transfer systems, and the one product in this range approved for both direct food contact (Class HT1) and incidental contact (H1).

32 cSt	0.869	218 °C	-18 °C
Viscosity @ 40°C	Density @ 15°C g/mL	Flash point	Pour point

APPLICATION

- Jacketed cooking and process vessels
- Fryers and direct heat process systems
- Closed circuit thermal fluid heating
- Applications requiring an HT1 classified fluid

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

All	components are FDA compliant
Contains	no genetically-modified ingredients, no nut oil or derivative
Kosher	certified
Pareve	certified
Halal	certified
Manufactured	to FLT Quality Standards and Good Manufacturing Practice

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

FOOD GRADE · FOOD GRADE HEAT TRANSFER OILS · CONTINUED

SARFOOD HEAT TRANSFER OIL 32.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear and Bright**
Density @ 15°C g/mL		**0.869**
Viscosity @ 40°C	cSt	**32**
Flash Point	°C	**218**
Fire Point	°C	**256**
Pour Point	°C	**-18**
Max. Oil Film Temperature	°C	**340**
Max. Bulk Oil Temperature	°C	**325**
Coefficient of Thermal Expansion % /	°C	**0.0915**
Coefficient of Thermal Expansion per	°C	**0.000760**

Typical values, not a specification.

PACK SIZES

5 L | 20 L | 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963