FOOD GRADE · FOOD GRADE CHAIN OILS

SARFOOD HT CHAIN LUBE 320.

A food grade chain lubricant for very high temperature service - rated to 300 °C continuous and 320 °C for short periods, on a highly polar biodegradable base oil.

220 cSt	315 °C	-36 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Bakery and biscuit oven chains
- Pasteuriser and retort conveyor chains
- High temperature drying and proving tunnels
- Chains running where ordinary oil carbonises

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

All	ingredients are FDA listed, grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives
Meets	the requirements of NSF and InS H1 Guidelines, the USDA 1998 H1 Guidelines

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear liquid**
Viscosity @ 40°C	cSt	**220**
Temperature Range Up to 320°C for short periods	°C	**-35 to 300**
NOACK Weight Loss after 1hr at 250°C	%	**<2**
Flash Point (COC)	°C	**315**
Pour Point	°C	**-36**
Auto-Ignition Temperature	°C	**350**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963