FOOD GRADE · FOOD GRADE GREASES

SARFOOD HTS 2 GREASE.

A PAO and polymer grease on a modified inorganic bentone thickener, with a drop point above 280 °C.

APPLICATION

- Hot bearings on long relubrication intervals
- Oven and dryer bearing points
- High water resistance requirements
- Where a soap grease would melt out

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

All	ingredients are FDA listed
Meets	NSF and InS H1 Guidelines, USDA 1998 H1 Guidelines
Contains	no genetically-modified ingredients, nut oil, or derivatives

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Off white smooth grease**
NLGI Classification		**No.2**
Thickener		**Bentone**
Drop Point (ASTM D2295)	°C	**> 280**
Oil separation % loss (ASTM D1742)		**2.5**
Copper Corrosion (ASTM D4048)		**1B**
Water washout (ASTM D1264) @ 38°C		**< 2% max.**
Four Ball Weld Load (IP 239)		**315kg**
Four Ball Wear (IP 239)	mm	**0.70**
Operating Temperature Range	°C	**-40°C to + 160**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963