

## Practical – 5

### AIM:

Demonstrate various Ways to handle Events

### HTML Source Code:

```
<!DOCTYPE html>
<html lang="en"> <head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head> <body>
  <h1>Change Message</h1>
  <input type="text" id="myInput" onclick="alert('Input was clicked!')"
onblur="alert('Input lost focus!')" onmouseover="alert('Mouseover on
Input!')" onkeypress="alert('key pressed!')" >

  <script src="./Events.js"></script>
</body>
</html>
```


**Javascript Source code:**

```
const input = document.querySelector("#myInput");
input.addEventListener("click", handleClick);
input.addEventListener("blur", handleBlur);
input.addEventListener("mouseover", handleMouseOver);
input.addEventListener("keypress", handleKeyPress);

function handleClick() { console.log("Input
    was clicked!");
}    function    handleBlur()    {
console.log("Input lost focus!");
}
function handleMouseOver() { console.log("Mouseover
    on Input!");
```

```
} function handleKeyPress(e) {
console.log("Key pressed:" + e.key);
}
```

**Output:**



**AIM:**

Write the Script to Change the background color randomly after every 1 mins

**HTML Source Code:**

```
<!DOCTYPE html>
<html lang="en"> <head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Change Background Colour</title>
  <script src="./background.js"></script>
</head>

<body> </body> </html>
```

**Javascript Source code:**


```
let colors = ['red', 'orange', 'yellow', 'green', 'blue', 'indigo',
'violet'];

let currentIndex = 0;
function changeColor() { let body =
document.querySelector('body');

  body.style.backgroundColor = colors[currentIndex];

  currentIndex = (currentIndex + 1) % colors.length;
} setInterval(changeColor,
60000);
```

**Output:**



**AIM:**

**Create Arrays of Colors and Apply these colors in order to tr background of table**

**HTML Source Code:**

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Change Table Colour</title>
  <style> table,td{
    border: solid black;
  }
</style>
</head>
<body>
  <h2>Change Table Colour</h2>
  <label for="colorInput">Colour Number:</label>
  <input type="number" id="colorInput">
  <button onclick="changeTableColor()">Change Table Colour</button>
  <br><br>
  <table id="myTable">
    <tr>
      <td>ID</td>
      <td>Name</td>
      <td>Age</td>
    </tr>
    <tr>
      <td>1</td>
      <td>abc</td>
      <td>19</td>
    </tr>
  </table>
  <script src="./colors in order.js"></script>
</body>
</html>
```

**Javascript Source code:**

```
var colors = ["red", "orange", "yellow", "green", "blue", "indigo", "violet"];
var currentIndex = 0;

function changeTableColor() { var table =
    document.getElementById("myTable"); var colorInput =
    document.getElementById("colorInput").value; var color =
    colors[colorInput - 1]; table.style.backgroundColor = color;
}
```

**Output:**

## Change Table Colour

Colour Number:

ID	Name	Age
1	abc	19

**AIM:**

Zoom image on mouseover and zoom out on mouse out

**HTML Source Code:**



```
<!DOCTYPE html>
<html lang="en"> <head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>



  
  <script src="./zoomImage.js"></script>
</body>
</html>
```

#### Javascript Source code:

```
function zoomIn() { var image = document.getElementById('myImage');
  image.style.width = "98%"; image.style.height = "98%";
}

function zoomOut() { var image = document.getElementById('myImage');
  image.style.width = "60%"; image.style.height = "60%";
}
```

#### Output:



**AIM:**

Change the location of image based on arrow key of keyboard using callback function

**HTML Source Code:**

```
<!DOCTYPE html>
<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Move Image</title>

</head>

<body>
```

```
  

  <script src="./locImg.js"></script>

</body>
</html>
```

**Javascript Source code:**

```
let img = document.getElementById("myImage");

document.addEventListener("keydown", moveImage);

function moveImage(event) {

    switch (event.keyCode) {

        case 37:
            img.style.left = (img.offsetLeft - 10) + "px";

            break;

        case 38:
            img.style.top = (img.offsetTop - 10) + "px";

            break;

        case 39:
            img.style.left = (img.offsetLeft + 10) + "px";

            break;
```

```
    case 40:  
img.style.top = (img.offsetTop + 10) + "px";  
  
    break;  
  
}  
  
event.preventDefault();  
}
```

**Output:****Conclusion:**

A callback function is a function passed into another function as an argument, which is then invoked inside the outer function to complete some kind of routine or action. A timer is used to execute some task after a particular time interval.