CoolPAK™ R6563

Long-term Indoor Storage Corrosion Inhibitor

Modern corrosion inhibitor offers long-term indoor storage protection. Low viscosity allows it to be used as an immersion bath for treatment of hollow parts. Can also be applied by spraying, flooding or rolling. For steel and other metals.

Application Guidelines

- VCI films suitable: The full corrosion protection is only given in the solvent-free film, therefore a short storage time until the solvent evaporates must be observed, especially before packing in boxes with film.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at https://www.masterfluids.com/eu/en/distributors/index.php, your District Sales Manager, or call our Tech Line at +49 211 41 72 8 -900.

Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Medium-brown, clear	Visual
Density at 15°C:	0.81 g/cm^3	ASTM D 7042
Viscosity at 20°C:	2.2 mm^2/s	ASTM D 7042
Flash point:	> 45 °C	DIN EN ISO 2719
Film weight:	1.3 g/m^2	Dipping procedure
Film type:	Oily	Haptical
Dewatering effect:	≤ 30 s	Internal test method
Water separation:	4 min	Internal test method
Humidity test:	120 cycles	DIN EN ISO 6270-2 AHT
Salt spray performance:	48 h	DIN EN ISO 9227 NSS

Additional Information

- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. Contact your Master Fluid Solutions' District Sales Manager for the latest version of this document. CoolPAK™ is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.

Choose CoolPAK R6563:

- Easily removable with organic solvents (cold cleaners) or water-miscible alkaline industrial cleaners
- Water displacing with very good wetting behaviour
- Extremely low additive loss due to water contact
- Stable against acidic and alkaline impurities
- Good for long-term indoor storage
- Good for overseas transport
- Good material compatibility

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions or from your Master Fluid Solutions' Authorised Distributor.

Packaging

1000-litre IBC
SKU: CPR6563/1000L

Master Fluid SOLUTIONS™

©2020-2024 Master Fluid Solutions™ | 2024-08-05

Master Fluid Solutions WDG GmbH
Hasselsstraße 6-14
Düsseldorf, 40597
Germany

+49 211 41 72 82 00
info-eu@masterfluids.com
masterfluids.com/eu/en/