OFF-HIGHWAY & AGRICULTURE

AGRISTAR SHPD 15W40.

A heavy-duty diesel engine oil for agricultural and off-highway vehicles, formulated for maximum drain intervals with a strong detergent/dispersant package for engine cleanliness under demanding conditions.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

94.1 cSt	13.6 cSt	0.881	>200 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15	Flash point

APPLICATION

- Euro 3 and Euro 4 heavy-duty diesel engines without after-treatment systems
- Certain Euro 5 engines without particulate filters
- Heavy-duty truck and bus applications

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	E7, E5
API	CI-4, SL
JASO	DH-1
Mercedes-Benz	228.3
MAN	3275
Volvo	VDS 3
Renault RVI	RLD-2
Mack	E-OM Plus
Cummins	20077/78
MTU	Type 2
Caterpillar	ECF-1a
Deutz	DQC III

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Specific Gravity @ 15°C		**0.881**
Kinematic Viscosity @ 40°C, cSt		**94.1**
Kinematic Viscosity @ 100°C, cSt		**13.6**
Viscosity Index	ASTM D2270	**146**
Pour Point, °C	ASTM D97	**-30**
Flash Point, °C	ASTM D92	**>200**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0410

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063