OFF-HIGHWAY & AGRICULTURE

AGRISTAR STOU 10W-30.

A Super Tractor Oil Universal, one oil for the engine, the transmission, the hydraulics and the wet brakes.

PRODUCT RANGE
Super Universal Tractor Oils

APPLICATION

- The lightest STOU grade, easier cold starting and lower drag
- Mixed farm fleets consolidating onto one oil
- Winter and shoulder-season work
- Tractors specified for a 10W-30 multifunctional

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 14 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CG-4/SF, GL-4
ACEA	E3
Massey Ferguson	M1139, M1144, M1145
John Deere	J20C, J20D, J27
FORD NEW HOLLAND	M2C-134D, M2C-159B/C
CASE Int.	MS-1204/6/7/9
CASE New Holland	MAT 3535, 3526
New Holland	NH 410B
Caterpillar	TO-2
Allison	C-4
FORD New Holland	82009201/2/3
ZF	TE-ML 06A, 06B, 06C, 06D, 07B
Mercedes-Benz	227.1, 228.1

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Specific Gravity @ 15.6°C		**0.877**
Kinematic Viscosity @ 100°C, cSt		**10.9**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0406

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063