OFF-HIGHWAY & AGRICULTURE

# AGRISTAR UHPD 15W40.

A semi-synthetic, low-SAPS heavy-duty diesel engine oil for the latest emission-controlled agricultural and off-highway engines, giving strong soot handling and oxidation control alongside broad OEM approval coverage.

PRODUCT RANGE

**Heavy Duty Diesel Engine Oils**

| 13.5 cSt | 0.864 | >220 °C |
|---|---|---|
| Viscosity @ 100°C | Specific Gravity @ 15 | Flash point |

## APPLICATION

- Euro 5 and Euro 6 emission-controlled diesel engines
- Case New Holland, Hitachi, Isuzu, JCB, John Deere, Kobelco, Komatsu and Liebherr plant

**NOT RECOMMENDED**

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

## BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 14 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **API** | CK-4 |
| **ACEA** | E11, E7, E9 |
| **JASO** | DH-2 |
| **Volvo** | VDS 4.5 |
| **Renault RVI** | RLD-3 |
| **Mack** | EO-S 4.5 |
| **Mercedes-Benz** | 228.31 |
| **Cummins** | CES 20086 |
| **MAN** | M3575 |
| **MTU** | Type 2.1 |
| **Caterpillar** | ECF-3 |
| **Deutz** | DQC-III-10 LA |

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Specific Gravity @ 15°C | | **0.864** |
| Kinematic Viscosity @ 100°C, cSt | | **13.5** |
| TBN | ASTM D2896 | **10.5** |
| Flash Point, °C | ASTM D92 | **>220** |
| Sulphated Ash, % | ASTM D874 | **<1.0** |

Typical values. They do not form a specification.

## PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0412

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063