OFF-HIGHWAY & AGRICULTURE

AGRISTAR ULTRA UHPD 10W40.

A full-synthetic, low-SAPS heavy-duty diesel engine oil for the latest emission-controlled off-highway engines, formulated for extended drain intervals and strong protection against bore polishing and cam wear.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

83.1 cSt	13.1 cSt	0.859	189 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15	Flash point

APPLICATION

- Euro 4, Euro 5 and Euro 6 diesel engines with DPF or SCR after-treatment
- Modern off-highway plant and equipment under severe operating conditions

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 11 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	E7, E8, E11, E6, E9
API	CK-4
Mercedes-Benz	228.51
Volvo	VDS 4.5
Renault RVI	RLD-3
MACK	EO-S 4.5
MAN	M3477, M3271-1
CAT	ECF-3
Cummins	CES 20076, 20077
Deutz	DQC III-10 LA
DAF	extended drain requirement

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Specific Gravity @ 15°C		**0.859**
Kinematic Viscosity @ 40°C, cSt		**83.1**
Kinematic Viscosity @ 100°C, cSt		**13.1**
Viscosity Index	ASTM D2270	**159**
Pour Point, °C	ASTM D97	**-40**
Flash Point (closed), °C		**189**
Sulphated Ash, %	ASTM D874	**<1.0**
TBN	ASTM D2896	**10.5**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0411

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063