OFF-HIGHWAY & AGRICULTURE

AGRISTAR UTTO HY-SYNTH.

The synthetic UTTO, and the one to specify where the machine is new, expensive or worked hard.

PRODUCT RANGE
Universal Tractor Transmission Oils

7.6 cSt	0.861	40 °C
Viscosity @ 100°C	Specific Gravity @ 15	Pour point

APPLICATION

- Late-model tractors under warranty
- Hydrostatic transmissions and CVT drives
- Cold-start critical operations
- High-hour contracting fleets on extended drains

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 16 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

OFF-HIGHWAY & AGRICULTURE · CONTINUED

AGRISTAR UTTO HY-SYNTH.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-4
AGCO-Allis	
Allis-Chalmers	PF-821XL
CASE	MS-1204, 1206, 1207, 1209
CASE New Holland	MAT 3509, 3525, 3526
CLAAS	/ Renault Agriculture requirement
New Holland	NH 405B, NH410B
John Deere	J20C, J20D
Ford	M2C-134D, FNHA 2C 201.00/200.00
Komatsu	AXO 80
Kubota	UDT, Super UDT
Massey Ferguson	M1143, M1145
McCormick	HTX
VALTRA	G2-08
Volvo	WB102 (97304)
ZF	TE-ML 03E, 03L, 05F, 17E, 21F

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Specific Gravity @ 15°C		**0.861**
Kinematic Viscosity @ 100°C, cSt		**7.6 (typical)**
Pour Point	ASTM D97	**40**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0420

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063