INDUSTRIAL OILS

AIRLINE LUBRICANT EP22.

A light, clean-burning oil for in-line lubricators feeding pneumatic tools.

PRODUCT RANGE
Vacuum & Airline Oils

APPLICATION

- Airline lubricators feeding impact wrenches and hammers
- Rotary vane air motors
- Assembly line pneumatic tooling
- Rock drills and pneumatic breakers

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Pale straw coloured, clear liquid**
Density @ 20°C	ISO 22241-2	**0.856 kg/m3**
Kinematic Viscosity @ 40°C, cSt		**22**
Kinematic Viscosity @ 100°C, cSt		**4.2**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AIR0022

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063