GREASES

ALUMINIUM COMPLEX EP2 MOLY.

An aluminium complex grease.

PRODUCT RANGE

Aluminium Complex Greases

APPLICATION

- Mining and quarrying plant
- Steel industry bearings
- Heavy construction and excavation
- Wet, shock-loaded applications

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth, adhesive grease**
Colour	ASTM D1500	**Grey/black**
NLGI Classification		**2**
Thickener		**Aluminium Complex**
Base Oil		**Solvent Refined Mineral Oil**
Solid Lubricant		**Molybdenum Disulphide**
Water resistance		**Fully resistant**
Water washout (IP 215), %		**<0.5**
Dropping point		**230°C min**
Copper Corrosion (IP 112)		**1b**
Resistance To Corrosion Emcor (IP 220)		**0 : 0**
Four Ball Weld Load (IP 239) kgs		**315**
Timken OK Load (IP 326) kgs		**20**
Operating Temperature Range, °C		**-20°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0300

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063