GREASES

ALUMINIUM EP2 COMPLEX.

An aluminium complex grease.

PRODUCT RANGE

Aluminium Complex Greases

APPLICATION

- Wet and water-saturated bearings
- Steel mill and rolling mill applications
- Agricultural, civil engineering and off-road plant
- Long-life greasing in wet conditions

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Smooth adhesive grease**
Colour	ASTM D1500	**Orange sparkle**
NLGI Classification		**2**
Thickener		**Aluminium Complex**
Base Oil		**Solvent Refined Mineral Oil**
Water washout (IP 215), %		**<0.5**
Water resistance		**Fully resistant**
Dropping point		**230°C min**
Copper Corrosion (IP 112)		**1b**
Resistance To Corrosion Emcor (IP 220)		**0 : 0**
Four Ball Weld Load (IP 239) kgs		**315**
Timken OK Load (IP 326) kgs		**20**
Operating Temperature Range, °C		**-20°C to +150**

Typical values. They do not form a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0912

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063