AUTOMATIC TRANSMISSION FLUIDS

AUTOTRANS 134 FE.

AUTOTRANS 134 FE is a premium, fully synthetic, low viscosity automatic transmission fluid developed to meet the requirements of the latest Mercedes-Benz 7G-Tronic Plus transmissions.

PRODUCT RANGE
OEM-Specific ATF

4.7 cSt	0.840	-49 °C	Blue
Viscosity @ 100°C	Specific Gravity @ 15.6	Pour point	Appearance

APPLICATION

- Mercedes-Benz 722.9+
- 722.9FE+ 7-speed transmissions
- hybrid 724.2 transmissions

NOT RECOMMENDED

- × Transmissions specifying a fluid type not listed in the approvals above
- × Use as a hydraulic or gear oil unless the OEM explicitly permits it

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement

PERFORMANCE PROFILE

Suitable where the following specifications are required:

MB	236.15, A001 989 78 03 09
ATF	134 FE

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Blue**
Specific Gravity @ 15.6°C		**0.840**
Kinematic Viscosity @ 100°C		**4.7 cSt (typical)**
Pour Point, °C	ASTM D97	**-49**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0071

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063