AUTOMATIC TRANSMISSION FLUIDS

AUTOTRANS DCT/DSG FLUID.

AUTOTRANS DCT/DSG FLUID is a very high performance, fully synthetic formulation developed to meet the requirements of the latest wet-clutch DCT (Dual Clutch Transmission) and DSG (Direct Shift Gearbox) units fitted in ma

PRODUCT RANGE
DCT & CVT Fluids

7.7 cSt	0.845	199 °C	-50 °C
Viscosity @ 100°C	Specific Gravity @ 15	Flash point	Pour point

APPLICATION

- VW DSG transmissions
- AUDI DSG transmissions
- SKODA DSG transmissions
- SEAT DSG transmissions
- BMW DCT transmissions
- MERCEDES-BENZ DCT transmissions
- VOLVO DCT transmissions
- FORD DCT transmissions
- ZF wet-clutch transmissions
- Borg Warner wet-clutch transmissions
- Getrag wet-clutch transmissions

NOT RECOMMENDED

- × Transmissions specifying a fluid type not listed in the approvals above
- × Use as a hydraulic or gear oil unless the OEM explicitly permits it

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 31 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

AUTOMATIC TRANSMISSION FLUIDS · CONTINUED

AUTOTRANS DCT/DSG FLUID.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ATF	BOT 450, BOT 341, FFL-2, FFL-3, FFL-4, TF DCT-F3
BMW	7 Speed (Getrag) / DCTF-1, DCTF-1+, DCTF-2, 6-speed DCT, MTF LT-5
FERRARI	7 Speed (Getrag) / TF DCT-3
FIAT	9.55550-HE2, 9.55550-MZ6
FORD	Powershift (6 Speed)
M2C 936A	
MERCEDES-BENZ	236.21 (7G-DCT)
MITSUBISHI	Dia-Queen SSTF-1
PEUGEOT/CITROEN	PSA 9734.S2
PORSCHE	PDK 999.917.080.00, PDK 999.917.080.01
RENAULT	EDC 6 speed (Getrag)
EDC	7
VOLVO	Powershift 6 Speed (GFT)
VW/AUDI	G 052 182 A2, G 052 182 A6, G 052 536, G 055 536, G 052 512, G 052 529 A2/A6 (S-Tronic), G 055 529 (ZF)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Amber**
Specific Gravity @ 15°C		**0.845**
Kinematic Viscosity @ 100°C		**7.7 cSt (typical)**
Flash Point COC, °C		**199**
Pour Point, °C	ASTM D97	**-50**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0069

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063