AUTOMATIC TRANSMISSION FLUIDS

AUTOTRANS SYNTH HEAVY DUTY PLUS.

The current-generation heavy duty automatic fluid, carrying Allison TES-668, the specification that replaced TES-295 and demands significantly better oxidation and shear stability for the longest drain intervals Allison

PRODUCT RANGE
Heavy Duty ATF

187 °C	-43 °C	Red
Flash point	Pour point	Colour

APPLICATION

- Allison TES-668 transmissions
- Latest generation bus and refuse vehicle automatics
- Maximum drain interval programmes
- Mercedes-Benz 236.91 applications

NOT RECOMMENDED

- × Transmissions specifying a fluid type not listed in the approvals above
- × Use as a hydraulic or gear oil unless the OEM explicitly permits it

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 19 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Allison	TES-668, TES-295, C4
DTFR	13C190 (MB 236.91), 13C180 (MB 236.9)
MAN	339 Z1, 339 V1, 339 Z2
Voith	H55.6335.xx
VOLVO	97340, 97341 (AT101)
ZF	TE-ML 02F, TE-ML 03D, TE-ML 04D, TE-ML 14A, TE-ML 14B, TE-ML 17C, TE-ML 20B, TE-ML 20C

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Red**
SG @ 100°C		**0.854**
KV @ 100°C, cSt		**7.6**
Flash Point, °C		**187**
Pour Point, °C	ASTM D97	**-43**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0076

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063