AUTOMATIC TRANSMISSION FLUIDS

AUTOTRANS SYNTH HEAVY DUTY.

The commercial vehicle automatic fluid: Allison TES-295 alongside C4, plus Voith, Volvo AT101, MAN, Mercedes-Benz 236.9 and the ZF TE-ML listings that cover bus and truck automatics.

PRODUCT RANGE
Heavy Duty ATF

7.6 cSt	0.844	187 °C	–43 °C
Viscosity @ 100°C	Specific Gravity @ 15	Flash point	Pour point

APPLICATION

- Bus and coach automatic transmissions
- Allison TES-295 applications
- Voith retarders and transmissions
- Heavy vehicle automatics on extended drain

NOT RECOMMENDED

- × Transmissions specifying a fluid type not listed in the approvals above
- × Use as a hydraulic or gear oil unless the OEM explicitly permits it

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 9 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

GM	Dexron IIIH, IIIG, IIE
FORD	Mercon V
Allison	C4, TES-295
Voith	H55.6336 (G1363)
VOLVO	97340, 97341 (AT101)
MB	236.9
CAT	TO-2
MAN	339 Z1, V1, Z2
ZF	TE-ML 02F, 03D, 14A, 14B, 17C, 20B, 20C

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Red**
Specific Gravity @ 15°C		**0.844**
Kinematic Viscosity @ 100°C, cSt		**7.6**
Flash Point, °C		**187**
Pour Point, °C		**–43**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0070

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063