AUTOMATIC TRANSMISSION FLUIDS

AUTOTRANS SYNTH.

A synthetic multi-vehicle ATF with one of the broadest approval lists in the range, GM Dexron IIIH/IIIG, Ford Mercon, Mercedes-Benz 236.1 through 236.10, BMW, Jaguar, Porsche, PSA AL4, Toyota, Hyundai/Kia, Voith, Volvo,

PRODUCT RANGE
Multi-Vehicle ATF

7.5 cSt	0.854	195 °C	–51 °C
Viscosity @ 100°C	Specific Gravity @ 15	Flash point	Pour point

APPLICATION

- Workshops consolidating multiple ATF part numbers
- Conventional 4, 5 and 6-speed automatics
- European and Japanese passenger cars
- ZF 5HP family transmissions

NOT RECOMMENDED

- × Transmissions specifying a fluid type not listed in the approvals above
- × Use as a hydraulic or gear oil unless the OEM explicitly permits it
- × CVT or DCT transmissions

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 22 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

AUTOMATIC TRANSMISSION FLUIDS · CONTINUED

AUTOTRANS SYNTH.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

GM	Dexron IIIH, IIIG
FORD	Mercon, M2C-138CJ, M2C-166H
ALLISON	C4, TES-389
ATF	3403, M115, LA2334, LT71141
BMW	LA2634, LT71141, 7045E, ETL-8072B
CAT	TO-2
CHRYSLER/JEEP/DODGE	ATF +2, ATF +3
HYUNDAI/KIA	SPII
JAGUAR	ATF 3403, M115, JLM 20238, JLM 20292
MAZDA	ATF M-III, F-1
MB	236.1, 236.5, 236.6, 236.7, 236.9, 236.10
MAN	339 Z1, V1, Z2, V2
PORSCHE	000 043 205 09
PSA	(PEUGEOT/CITROEN) AL4
RENAULT	DPO/AL4
TOYOTA	ATF D-III
VOITH	55.6335, 55.6336
VOLVO	97335, 97340, 97341 (AT101)
VW	G 052 162 A2
ZF	TE-ML 02F, 03D, 05L, 09, 21L, 3 & 4 speed auto transmissions, 5HP 18FL/19FL/24/24A/30

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Red**
Specific Gravity @ 15°C		**0.854**
Kinematic Viscosity @ 100°C, cSt		**7.5 (typical)**
Flash Point, °C		**195**
Pour Point, °C		**–51**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0065

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063