AUTOMATIC TRANSMISSION FLUIDS

AUTOTRANS TYPE G.

A Type G fluid, non friction-modified, which is the whole distinction.

PRODUCT RANGE
OEM-Specific ATF

7.4 cSt	0.865	>200 °C	Red
Viscosity @ 100°C	Specific Gravity @ 15	Flash point	Appearance

APPLICATION

- Ford Type G specified transmissions
- John Deere J21A applications
- Older non friction-modified automatics
- Where a Dexron fluid must not be used

NOT RECOMMENDED

- × Transmissions specifying a fluid type not listed in the approvals above
- × Use as a hydraulic or gear oil unless the OEM explicitly permits it

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement

PERFORMANCE PROFILE

Suitable where the following specifications are required:

FORD	ESP M2C-33G, ESP M2C-33F
John Deere	J21A

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Red**
Specific Gravity @ 15°C		**0.865**
Kinematic Viscosity @ 100°C, cSt		**7.4 (typical)**
Flash Point, °C		**>200**
Copper Corrosion	ASTM D130	**Nil**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0066

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063