AUTOMOTIVE

AXLE-PRO GEAR OILS 80W-140 GL-5.

A premium API GL-5 / MT-1 hypoid axle oil carrying the full modern heavy-duty approval set, including SAE J2360, which is the one that actually means something.

PRODUCT RANGE
Gear & Axle Oils

383.3 cSt	28.0 cSt	0.906
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6

APPLICATION

- Heavily loaded axles and hot running
- Tipper, mixer and heavy haulage work
- High torque, low speed final drives

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 16 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-5, MT-1
MIL-PRF	2105E
SAE	J-2360
SCANIA	STO 1:0
MACK	GO-J
Arvin	Meritor Axles
MAN	342 Type M2
MB	235.20 (80w90)
ZF	TE-ML 05A, TE-ML 07A, TE-ML 12E, TE-ML 16B, TE-ML 17B, TE-ML 19B, TE-ML 21A

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.906**
Viscosity @ 40°C, cSt		**383.3**
Viscosity @ 100°C	ASTM D445	**28.0 Cst**
Viscosity Index	ASTM D2270	**104**

Typical values. They do not form a specification.

PACK SIZES

20 L; 205 L; 1000 L IBC; Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0660

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063