AUTOMOTIVE

# AXLE-PRO GEAR OILS 80W-90.

A premium API GL-5 / MT-1 hypoid axle oil carrying the full modern heavy-duty approval set, including SAE J2360, which is the one that actually means something.

PRODUCT RANGE
**Gear & Axle Oils**

| 205.3 cSt | 15.0 cSt | 0.899 |
|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Density @ 15.6 |

## APPLICATION

- The standard heavy-duty axle fill
- Commercial vehicle drive axles
- General haulage and distribution fleets

**NOT RECOMMENDED**

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

## BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 16 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **API** | GL-5, MT-1 |
| **MIL-PRF** | 2105E |
| **SAE** | J-2360 |
| **SCANIA** | STO 1:0 |
| **MACK** | GO-J |
| **Arvin** | Meritor Axles |
| **MAN** | 342 Type M2 |
| **MB** | 235.20 (80w90) |
| **ZF** | TE-ML 05A, TE-ML 07A, TE-ML 12E, TE-ML 16B, TE-ML 17B, TE-ML 19B, TE-ML 21A |

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Density @ 15.6°C | | **0.899** |
| Viscosity @ 40°C, cSt | | **205.3** |
| Viscosity @ 100°C, cSt | ASTM D445 | **15.0** |
| Viscosity Index | ASTM D2270 | **105** |

Typical values. They do not form a specification.

## PACK SIZES

20 L; 205 L; 1000 L IBC; Bulk

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0650

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063