SAR Lubricants

SPECIALITIES

CHAIN & GEAR LUBE SPRAY.

Tacky aerosol chain lubricant that sprays thin to penetrate the link, then sets to a clinging film that resists fling-off at speed.

PRODUCT RANGE
Aerosols & Sprays

APPLICATION

- Drive and conveyor chains
- Motorcycle final drive chains
- Open gears and sprockets

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Industrial	chain grade

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Type		**Adhesive chain lubricant**
Base Oil Viscosity, °C	ASTM D445	**220 cSt @ 40**
Fling Resistance		**High**
Temperature Range, °C		**-10 to +150**
Penetration		**Low viscosity on application**

Typical values. They do not form a specification.

PACK SIZES

400 ml aerosol, 500 ml aerosol, 12 x 500 ml case

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS on request

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063