SPECIALITIES

Chain Lube Aerosol.

A PTFE-fortified chain lubricant aerosol with anti-fling tackifiers to stay on the chain rather than being thrown off in use, safe on O-rings.

PRODUCT RANGE
Aerosols & Sprays

APPLICATION

- medium and heavily loaded chain drives
- wide operating temperature range, -30°C to +180°C (peak +200°C)

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PACK SIZES

500ml aerosol in box of 12

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS ARCHL500

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063