INDUSTRIAL OILS

CHAIN LUBE SYNTH 280.

A synthetic ester chain lubricant for hot running, rated to 280 °C continuous and 300 °C for short periods.

PRODUCT RANGE
Chain Lubricants

APPLICATION

- Textile stenter and dryer chains
- Bakery and food oven conveyor chain
- Paint bake and powder coat lines
- Kiln car and furnace chain

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Straw-coloured liquid**
Viscosity @ 40°C, cSt		**135-165**
Temperature Range, °C	Up to 300°C for short periods	**-10 to 280**
NOACK weight loss after 1hr @ 250°C, %		**0.9**
Specific Gravity	ASTM D1298	**0.98**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IB0584

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063