AUTOMOTIVE

CLASSIC 20W-50.

High quality multigrade engine oil for classic car and motorcycle engines, aimed at vehicles from the mid-1950s to the early 1980s.

PRODUCT RANGE
Passenger Car Engine Oils

161.5 cSt	18.96 cSt	0.886	214 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Classic cars from the mid-1950s to early 1980s
- Classic motorcycle engines
- Show, rally and historic use

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	SJ/CF

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 20W-50**
Base Oil		**Mineral**
Kinematic Viscosity @ 40°C, cSt		**161.5**
Kinematic Viscosity @ 100°C, cSt		**18.96**
Viscosity Index	ASTM D2270	**132**
Flash Point, °C	ASTM D92	**214**
Pour Point, °C	ASTM D97	**-26**
Specific Gravity @ 15.6°C		**0.886**
TBN, mg KOH/g	ASTM D2896	**7.7**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0052

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063