AUTOMOTIVE

CLASSIC GEAR OIL SAE 90 GL-1.

A straight mineral, non-EP gear oil to API GL-1, no extreme pressure additive at all.

PRODUCT RANGE
Gear & Axle Oils

18.7 cSt	0.895	>230 °C	-15 °C
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Pour point

APPLICATION

- Vintage and veteran gearboxes
- Worm drives with phosphor bronze wheels
- Older industrial reduction gear
- Where a non-EP oil is specified

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-1

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Specific Gravity @ 15.6°C		**0.895**
Kinematic Viscosity @ 100°C, cSt		**18.7**
Flash Point COC, °C		**>230**
Pour Point, °C		**-15**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0090

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063