AUTOMOTIVE

CLASSIC SAE 30.

Monograde mineral engine oil for classic and vintage engines specifying a straight SAE 30.

PRODUCT RANGE
Passenger Car Engine Oils

APPLICATION

- Vintage and veteran engines
- Applications specifying a monograde

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Specification	on request

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 30**
Base Oil		**Mineral**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0053

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063