INDUSTRIAL OILS

COMPRESSOR OIL 68.

An ashless mineral compressor oil for reciprocating and rotary machines.

PRODUCT RANGE
Compressor Oils

67.7 cSt	8.9 cSt	0.887
Viscosity @ 40°C	Viscosity @ 100°C	Density

APPLICATION

- Reciprocating air compressors on 2,000 hour service
- Rotary vane compressors
- Workshop and general plant air supply
- Machines where the builder specifies DIN 51506 VDL

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51506 VDL (Piston Air Compressor Oils)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
SAE Viscosity No.		**20**
Viscosity @ 40°C		**67.7**
Viscosity @ 100°C	ASTM D445	**8.9**
Density		**0.887**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS CL0081

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063