INDUSTRIAL OILS

COMPRESSOR OIL SYNTH 100.

A full synthetic PAO compressor oil for operators who want to stop changing oil every few months.

PRODUCT RANGE
Compressor Oils

100 cSt	0.8	210 °C	-45 °C
Viscosity @ 40°C	Relative Density @ 15°C / 4	Flash point	Pour point

APPLICATION

- Rotary screw compressors on extended drain
- Continuously running plant air systems
- Unheated compressor houses
- Sites cutting compressor oil changes from 2,000 to 8,000 hours

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51506 (VDL)
ISO	DP 6521 (DAG)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Relative Density @ 15°C / 4°C		**0.8**
Pour Point, °C		**-45**
Flash Point, COC °C min		**210**
Viscosity, cSt @ 40°C		**100**
Rust (ASTM D 665 A)		**Pass**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS CLSYN0100

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063