GREASES

# COPPER ANTI-SEIZE COMPOUND.

A lead-free copper and graphite anti-seize compound rated to 1100 °C.

PRODUCT RANGE

**Anti-Seize & Assembly Compounds**

## APPLICATION

- Exhaust studs and manifold fasteners
- Brake caliper and hub bolts
- Flanged pipe connections at temperature
- Preventing galling on stainless assembly

### NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

## BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Colour & Appearance | | **Copper Coloured Smooth Paste** |
| NLGI Classification | | **1 to 2** |
| Thickener | | **Organically Modified Clay** |
| Dropping Point, °C | | **Above 260** |
| Lubricating Solids | | **Copper, Graphite** |
| Solids Content, % | | **23** |
| Electrical Conductivity | | **Excellent** |
| Anti-seize Temperature Range, °C | | **-30°C to 1100** |
| Coefficient Of Friction | | **0.12** |

Typical values. They do not form a specification.

## PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0860

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063