OFF-HIGHWAY & AGRICULTURE

DRIVE TRAIN FLUID TO-4 10W.

A Caterpillar TO-4 drive train fluid, and one of the few places in lubrication where using a better oil makes things worse.

PRODUCT RANGE
Drive Train Fluids

APPLICATION

- Cold climates and winter working
- Hydraulic systems calling for a TO-4 10W
- Machines specified 10W for the transmission

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 8 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Caterpillar	TO-4, TO-2
Allison	C4 (off road)
Euclid, Dana	
Termec	/ TTC
Komatsu	KES 07.868.1
Vickers	M-2950-S

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Dark amber liquid**
Density @ 15.6°C		**0.874**
Kinematic Viscosity @ 100°C, cSt		**4.78**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0062

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063