OFF-HIGHWAY & AGRICULTURE

DRIVE TRAIN FLUID TO-4M.

The multigrade answer to the TO-4 problem.

PRODUCT RANGE
Drive Train Fluids

14.1 cSt	0.871	-38 °C
Viscosity @ 100°C	Density @ 15.6	Pour point

APPLICATION

- Year-round operation without a seasonal change
- Mixed plant fleets on one drive train fluid
- Cold-start critical machines
- ZF TE-ML 03C transmissions

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-4
Caterpillar	TO-4M, TO-4
Allison	TES 439, C4 (off road)
ZF	TE-ML 03C

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Dark amber liquid**
Density @ 15.6°C		**0.871**
Kinematic Viscosity @ 100°C, cSt		**14.1**
Pour Point, °C		**-38**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AD0075

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063