INDUSTRIAL OILS

DUST SUPPRESSANT OIL.

A light mineral oil with selected additives for knocking airborne dust out of a process.

PRODUCT RANGE
Industrial Specialities

3.5 – 4.5 cSt	0.853	150 °C
Viscosity @ 40°C	Density @ 15.6	Flash point

APPLICATION

- Dust suppression on bulk handling and transfer points
- Powder and granular processing
- Reducing airborne dust in enclosed plant
- Explosive dust risk mitigation

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Pale, clear liquid**
Density @ 15.6°C		**0.853**
Closed Flash Point, °C		**150**
Kinematic Viscosity @ 40°C, cSt		**3.5 – 4.5**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS I00811

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063