INDUSTRIAL OILS

DYE DUST SUPPRESSANT 5LP.

A dust suppressant developed specifically for the dye industry, where airborne pigment is both a serious staining problem and a real exposure concern for operators handling powder dyestuffs.

PRODUCT RANGE
Industrial Specialities

3.5 – 4.5 cSt	0.82	200 °C
Viscosity @ 40°C	Density @ 15.6	Flash point

APPLICATION

- Powder dyestuff handling and weighing
- Dye house dust control
- Pigment blending operations

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Clear liquid**
Density @ 15.6°C		**0.82**
Closed Flash Point, °C		**200**
Kinematic Viscosity @ 40°C, cSt		**3.5 – 4.5**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS I00810

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063