GREASES

ELECTROSHIELD.

A dielectric silicone-type gel for electrical work, a grease whose purpose is to insulate rather than to lubricate.

PRODUCT RANGE
Speciality Greases

300 °C	None	2.5
Flash point	Dropping point	NLGI grade

APPLICATION

- Electrical connectors and terminals
- Battery terminals and bulb holders
- Spark plug boots and ignition components
- Switchgear and outdoor electrical enclosures

NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**White translucent gel**
NLGI Classification		**2.5**
Flash Point, °C	ASTM D92	**300**
Dropping point (IP132)		**None**
Copper Corrosion (IP112)		**Pass**
Worked penetration (IP50)		**240 to 270**
Operating temp. range, °C		**-55°C to +205**
Dielectric Strength at 25°C (ASTM D149)		**16kV/mm**
Dielectric Constant at 25°C (ASTM D150)		**2.8**
Permittivity at 25°C (ASTM D257)		**1.1015 ohms.cm**

Typical values. They do not form a specification.

PACK SIZES

100 g, 500 g, 3 kg

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0700

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063