SPECIALITIES

ENDURANCE LONG LIFE ANTIFREEZE.

A long-life OAT coolant concentrate, free from nitrites, amines, phosphates, borates and silicates.

PRODUCT RANGE
Antifreeze & Coolants

APPLICATION

- Modern cars and light commercials on a long-life fill
- Mixed fleets standardising on one OAT product
- Systems specified for VAG G12/G12+ or MB 325.3
- Extended service interval maintenance

NOT RECOMMENDED

- × Any use outside the stated dilution or application instructions
- × Mixing with a product of a different inhibitor technology

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system, aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 16 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Red/Orange Colour**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres available on request.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306
Chrysler	MS 9176
Cummins	85T8-2, 90T8-4
FORD	WSS-M97B44-D
GM/Saab	6277M, 1899M
John Deere	H24 B1/C1
Mack	014GS 17004
MAN	248, 324 Type SNF
Mercedes-Benz	325.3
MTU	MTL 5048
PSA	Group B71 5110
RENAULT	41-01-001-D
VAG	G12/G12+, TL 774-D/F
VOLVO	PENTA VCS
Suitable	for use where G30, G33 and G34 specification fluids are required

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AF0560

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063